

## 参考文献

- 1) Peel, H., Wade, C., Spearpoint, M., Fleischmann, C.: Experiments to develop a performance based assessment method for rooms partially lined with timber, 11th International Conference on Performance-Based Codes and Fire Safety Design Methods, 23-25 May, Warsaw, Poland, 2016.
- 2) 市原卓磨, 長谷見雄二, 安井昇, 鈴木淳一, 鍵屋浩司, 吉田正志: 木質内装材料の燃焼発熱性状に関する研究－大規模空間における火災成長率の実験的把握, 日本建築学会大会学術講演梗概集, pp. 319-322, 2012.
- 3) 国土交通省住宅局建築指導課他編: 2001 年版避難安全検証法の解説及び計算例とその解説, 海文堂, 2000.
- 4) 平成 12 年建設省告示第 1441 号, 階避難安全検証法に関する算出方法を定める件.
- 5) 出口嘉一, 長岡勉, 岡崎智仁, 白波瀬智幸: 避難安全検証法の内装制限の適用除外規定を活用した木質内装の実現, 日本建築学会技術報告集, Vol. 20, No. 45, pp. 599-604, 2014.
- 6) Quintiere, J. G., Harkleroad, M., Hasemi, Y.: Wall flames and implications for upward flame spread, Combustion Science and Technology, Vol. 48, No. 3/4, pp. 191-222, 1986.
- 7) Quintiere, J. G., Harkleroad, M., Walton, D.: Measurement of material flame spread properties, Combustion Science and Technology, Vol. 32, pp. 67-89, 1983.
- 8) 鈴木圭一, 田中哮義, 原田和典, 吉田治典: 火災空間における垂直温度分布の予測モデル—多層ゾーン煙流動予測モデルの開発 その 1-, 日本建築学会環境系論文集, Vol. 69, pp. 1-7, 2004.
- 9) Karlsson, B.: Modeling fire growth on combustible lining materials in enclosures, Report TVBB 1009 Lund University, Department of Fire Safety Engineering, 1992.
- 10) Quintiere, J. G.: A simulation model for fire growth on materials subject to a room-corner test, Fire Safety Journal, Vol. 20, pp. 313-339, 1993.
- 11) Wade, C. A., Barnett, J. R.: A room-corner fire model including fire growth on linings and enclosure smoke-filling, Journal of Fire Protection Engineering, Vol. 8, pp. 27-36, 1997.
- 12) Peel, H., Wade, C., Spearpoint, M.: Comparison of partially lined timber room experiments with the modified B-RISK flame spread capability, 14th International Conference and Exhibition on Fire Science and Engineering - Interflam 2016, 4-6 July, Royal Holloway College, Windsor, UK, 2016.
- 13) Lattimer, B. Y., Hunt, S. P., Wright, M., Sorathia, U.: Modeling fire growth in a combustible corner, Fire Safety Journal, Vol. 38, pp. 771-796, 2003.
- 14) 田中哮義, 中村和人: <二層ゾーンの概念に基づく>建物内煙流動予測計算モデル, 建築研究報告 No. 123, 建設省建築研究所, 1989.
- 15) Tanaka, T., Yamada, S.: BRI2002: Two layer zone smoke transport model, Fire Science and

Technology, Vol. 23, pp. 1-131, 2004.

- 16) Tanaka, T., Yamaguchi, J., Wakamatsu, T.: Investigations into flow rates of opening jet plumes from a fire space, Fire Safety Science, Vol. 6, pp. 1113-1124, 2000.
- 17) Yamana, T., Tanaka, T.: Smoke control in large scale spaces (part 2: smoke control experiments in a large scale space), Fire Science and Technology, Vol. 5, pp. 41-54, 1985.
- 18) 出口嘉一, 鍵屋浩司, 河合邦治, 山口純一: 実大規模の居室等における煙流動・排煙実験－(その2)自然排煙における給気口の効果－, 日本建築学会大会学術講演梗概集, pp. 105-108, 2018.
- 19) 吉田悠起, 西野智研, 鍵屋浩司: センサーデータを用いた建築火災時の即時煙流動推定に関する研究－その2 実大複数室煙流動実験への適用－, 日本建築学会大会学術講演梗概集, 2020.
- 20) 鈴木圭一, 田中哮義, 原田和典, 吉田治典: 区画火災の鉛直温度分布予測モデルの拡張と検証および火災ブルームへの連行を考慮した天井ジェット温度予測－多層ゾーン煙流動予測モデルの開発 その2－, 日本建築学会環境系論文集, Vol. 70, pp. 1-7, 2005.
- 21) Takahashi, W., Tanaka, H., Sugawa, O., Ohtake, M.: Flame and plume behavior in and near a corner of walls, Fire Safety Science, Vol. 5, pp. 261-271, 1997.
- 22) Sugawa, O., Tobari, M.: Behavior of flame/plume flow in and near corner fire –entrainment coefficient for corner fire–, U.S./Japan Government Cooperative Program on Natural Resources (UJNR). Fire Research and Safety. 15th Joint Panel Meeting. Vol. 2, pp. 489-493, 2000.
- 23) Zukoski, E., Kubota, T., Cetegen, B.: Entrainment in fire plume, Fire Safety Journal, Vol. 3, pp. 107-121, 1980/81.
- 24) Thomas, P. H., Hinkley, P. L., Theobald, C. R., Simms, D. L.: Investigations into the flow of hot gases in roof venting, Fire Research Technical Paper, No. 7, HMSO, London, 1963.
- 25) Heskestad, G.: Virtual origins of fire plumes, Fire Safety Journal, Vol. 5, pp. 109-114, 1983.
- 26) Cooper, L.Y., Harkleroad, M., Quintiere, J., Rinkinen, W.: An experimental study of upper hot layer stratification in full-scale multiroom fire scenario, Journal of Heat Transfer, Vol. 104, pp. 741-749, 1982.
- 27) Quintiere, J. G., Harkleroad, M.: New concepts for measuring flame spread properties, National Bureau of Standards (U.S.) NBSIR 84-2943, 1984.
- 28) 小宮祐人, 土橋常登, 原田和典, 仁井大策, 鍵屋浩司: CCM 装置を利用した内装材料の燃え拡がり試験方法に関する検討 (その2) 縮小 LIFT 試験結果, 日本建築学会大会学術講演梗概集, pp. 251-252, 2019.
- 29) 土橋常登, 小宮祐人, 原田和典, 仁井大策, 鍵屋浩司: CCM 装置を利用した内装材料の燃え拡がり試験方法に関する検討 (その1) 熱慣性と発熱特性の測定結果, 日本建築学会大会学術講演梗概集, pp. 249-250, 2019.
- 30) Hasemi, Y., Tokunaga, T.: Some experimental aspects of turbulent diffusion flames and buoyant

plumes from fire sources against a wall and in a corner of walls, Combustion Science and Technology, Vol. 40, pp. 1-18, 1984.

- 31) Lattimer, B. Y., Sorathia, U.: Thermal characteristics of fires in a noncombustible corner, Fire Safety Journal, Vol. 38, pp. 709-745, 2003.
- 32) Hasemi, Y., Yoshida, M., Yokobayashi, Y., Wakamatsu, T.: Flame heat transfer and concurrent flame spread in a ceiling fire, Fire Safety Science, Vol. 5, pp. 379-390, 1997.
- 33) Tanaka, T., Yamana, T.: Smoke control in large scale spaces (part 1: analytic theories for simple smoke control problems), Fire Science and Technology, Vol. 5, pp. 31-40, 1985.
- 34) McCaffrey, B. J., Quintiere, J. G., Harkleroad, M. F.: Estimating room temperatures and the likelihood of flashover using fire test data correlations, Fire Technology, Vol. 17, pp. 98-119, 1981.
- 35) Peel, H.: Fire development in rooms partially lined with timber, A thesis submitted in partial fulfilment of the requirements for the Degree of Master of Engineering in Fire Engineering in the University of Canterbury, University of Canterbury, 2016.
- 36) 長岡勉, 辻本誠, 古平章夫, 上原茂男, 菊池伸一: 木材の密度と着火時間の関係, 日本建築学会構造系論文集, Vol. 67, No. 559, pp. 233-236, 2002.
- 37) 原田寿郎: 木材の燃焼性および耐火性能に関する研究, 森林総研研報, No. 378, pp. 1-85, 2000.
- 38) Natori, A., Kakae, N., Kitahori, J., Tsuchihashi, T., Abe, T., Nagaoka, T., Ohmiya, Y., Harada, K.; Development of a simple estimation method of heat release rate based on classification of common combustibles into category groups, Fire Science and Technology, Vol. 25, pp. 31-54, 2006.
- 39) 後藤大輔, 大宮喜文: 区画内の化学種濃度及び伝熱量の変化に着目した火災性状予測, 日本建築学会環境系論文集, Vol. 74, No. 638, pp. 403-411, 2009.
- 40) Forney, G. P.; Computing radiative heat transfer occurring in a zone fire model, Fire Science and Technology, Vol. 14, pp. 31-47, 1994.
- 41) Hasemi, Y., Tokunaga, T.: Flame geometry effects on the buoyant plumes from turbulent diffusion flames, Fire Science and Techonology, Vol. 4, pp. 15-26, 1984.
- 42) McGrattan, K., Selepak, M., Hnetkovsky, E.: The influence of walls, corners and enclosures on fire plumes, National Institute of Standards and Technology Technical Note 1984, 2018.
- 43) 出口嘉一, 岸上昌史, 山崎慧, 大宮喜文: 垂直温度分布の多項式近似による高温層と低温層の温度境界面高さの簡易推定方法, 日本建築学会環境系論文集, Vol. 85, No. 772, pp. 413-423, 2020.
- 44) 田中哮義: 建築火災安全工学入門 第3版, 日本建築センター, p. 248, 2020.